

JM804H

DOUBLE DRUM ROAD **ROLLER** ENGINE BRAND YANMMAR
ENGINE MODEL 4TNV88
GROSS POWER 35 kW
OPERATING WEIGHT 4000 kg




JM804H DOUBLE DRUM ROAD ROLLER



TECHNICAL PARAMETERS

WEIGHT	Weight	Operating Weight	3900kg without	3900kg without ROPS/4000kg with ROPS	
	Compaction Characteristic	Static Liner Pressure	15.4 kg/cm		
	Drum Width		1300 mm		
DRUMS	Drum Diameter		800 mm		
ENGINE & DRIVE TRAIN	Engine	Brand	YANMAR		
		Model	4TNV88		
		Fuel	Diesel		
		Cooling	Water		
		Number of Cylinders	4		
		Rated Power	35 kW		
		Rated Speed	3000 rpm		
		Fuel Tank	130 L		
		Hydraulic Tank	95 L		
		Water Tank	230 L		
	Hydraulic Drive	Driving mode	Hydrostatic double drum drive		
		Driving motor	brand	Thoth	
			model	TMS05	
		Driving pump	brand	Poclain	
			model	PM2028	
		Gradeability	30%		
		Working Speed	0 – 5 km/h		
		Travelling Speed	0 – 11 km/h		
	Vibration	Vibration mode	Hydraulic drive, automatic vibration-		
			disengagement mechanism		
		Vibration motor	brand	Permco	
		Vibration pump	model	M097-8	
			brand model	Permco	
		Vibration frequency	model P097-9/3 68/54 Hz		
		Amplitude of vibration	0.35/0.6 mm		
		Centrifugal force	40/45 kN		
CABIN & CONTROLS	Electrical System		12 V		
	Brakes	Service Brake	Hydrostatic		
		Parking Brake	Electronic controlled multidisc brake in		
			both drums		
	Steering		Hydraulic power steering		
OVERALL DIMENSION	Overall Length		2550 mm		
	Overall Width		1400 mm		
	Overall Height		2650 mm		
	Turning Radius (outer)		4200 mm		
	Ground Clearance		240 mm		
	Wheel Base		1860 mm		
	Working Width		1400 mm		





JIANGSU JUNMA ROAD ROLLER CO., LTD.